



## SPACE TAG 20 MM HITAG 2

<b>Description:</b>	SPACE TAG 20mm HITAG 2		
<b>IC type:</b>	Hitag 2		
<b>Physical:</b>	Diameter:	20.00 mm	± 0.30 mm
	Thickness:	02.15 mm	± 0.20 mm
	Hole:	none	
	Weight:	02.00 g	± 0.50 g
	Material:	Polycarbonate	Dark Blue
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz
<b>Thermal:</b>	Storage temperatures:	-40°C up to 90°C	
	Operating temperatures:	-25°C up to 70°C	
<b>Chemical:</b>	Water immersion IP67		
	Aqueous solution of salts		
	Unleaded gasoline		
	Petroleum		
	Mineral and vegetable oil		
<b>Special:</b>	Upon request other chip technologies are available.		
<b>Part number:</b>	TAF-05-AA		

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.