

metraTec® PulsarMX UHF RFID Reader

The PulsarMX is a UHF RFID Reader for applications with medium read range between 2 and 5 m and up to 100 tags at the same time in the field (anti collision). Typical applications include container tracking, reading data from sensor tags or as a scanning station on a conveyor belt. With its low cost, it opens up new possibilities for RFID which were not economical before.

With its compact dimensions of only 130 x 106 x 55 mm and the low heat development the reader can be easily integrated into electrical cabinets and machines. The communication to the host system is done via USB or the integrated Ethernet interface. Other interfaces, such as WiFi, RS485 or even Fieldbus technology are available on request. The optically isolated inputs and 24V DC outputs allow connecting the device directly to a PLC and light barriers and LEDs.

Integration into IT systems based on Windows is supported by a .NET DLL and a Java SDK which can be downloaded from our website for free. A demo software is also available with a comprehensive set of features that allows easy testing of the device.


Applications

- Use at a conveyor belt or sorter
- Container Identification with direct connection to an ERP system
- Cool-Chain Monitoring with UHF sensor tags
- Identification of vehicles and loading equipment



Technical Specification

| | |
|-----------------------|--------------------------------------------------------------------------------|
| Operating Principle | UHF RFID Mid Range Reader |
| Operating Frequency | 868 MHz (ETSI UHF RFID) |
| Protocol | EPC Class 1 Gen 2 |
| Operating Voltage | 24 V DC |
| Power Consumption | up to 400 mA |
| Interfaces | USB, Ethernet, other on request |
| Inputs/Outputs | optically isolated 24 V DC Inputs (2x), 24 V DC Outputs (4x), 24 V DC Out (1x) |
| Antenna Connector | SMA, female |
| Read Range | up to 5 m (depending on antenna & tag) |
| RF Power | 27 dBm (500 mW) |
| Operating Temperature | -20°C - +75°C |
| Housing, IP | Aluminium, IP40 (higher on request) |
| Dimensions | 130 x 106 x 55 mm |
| Conformity | CE, e.g. EN 60950-1, ETSI 302 208 |



At a Glance

- Compact Form Factor
- Industrial Inputs/Outputs
- Best Value

About metraTec

metraTec develops, manufactures and sells hardware for the product segments „Identification“, „Localization“, „Communication“ and „Wireless Power“. It serves a variety of industries, both with standard products as well as custom solutions. Our customers are system integrators, OEM customers as well as research institutes world wide.

Contact

metraTec GmbH
 Werner-Heisenberg-Str. 1
 39106 Magdeburg, Germany

Tel.: +49 (0)391 251906-00

Fax: +49 (0)391 251906-01

Email: sales@metratec.com

Web: www.metratec.com